



iM2500

Storm

Carry-On Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin




CONFIGURATIONS



iM2500
Standard



iM2500-X0000
No Foam



iM2500-X0002
With Padded Dividers



iM2500-X0006
With TrekPak Divider System



iM2500-X0001
With Foam

DIMENSIONS

Interior (L×W×D)	20.50 x 11.50" x 7.20 (52.1 x 29.2 x 18.3 cm)
Exterior (L×W×D)	21.70 x 14.10" x 8.90 (55.1 x 35.8 x 22.6 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.20" (13.2 cm)
Total Depth	7.2" (18.3 cm)
Int Volume	0.98 ft ³ (0.028 m ³)
Padlock Hole Diameter	1/4" (2.5 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

■ Black

■ OD Green

■ Yellow

WEIGHT

Weight With Foam	13.70 lbs (6.2 kg)
Weight Empty	11.10 lbs (5 kg)
Buoyancy	62.56 lbs (28.4 kg)
Master Pack Weight	42.10 lbs (19.1 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	0.50" Pad
Layer 3 (Base)	1.62" Pick N Pluck
Layer 4 (Base)	1.62" Pick N Pluck
Layer 5 (Base)	1.62" Pick N Pluck

OTHER

Extendable Handle	yes
Master Pack	3
Military	yes

ACCESSORIES



iM2500-UTILITYORG
Utility Organizer




iM2500-FOAM
5 pc. Replacement Foam Set



iM2500-DIV
Padded Divider Set



iM2500-BEZEL-LID
Lid Bezel Kit



iM2500-BEZEL
Base Bezel Kit



iM-STRAP-S-VER2
Padded Shoulder Strap



iM-LIDSTAY
Lid Stay



iM2500TPKIT
TrekPak Case Divider Kit



1555TPDIV
Extra TrekPak Dividers



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-02-19